

ISVI.9



IP66	IK09	CREE XP-G	RECYCLE
FAILURE RATE < 0,1% after 25,000h	LIFE TIME Tested over 50,000h	MIN -20°C MAX 55°C	CLASE I
SP US	RoHS	CE	RoHS 2

CIRCULAR PROJECTORS
ISVI SERIES

References

Code	Type	Finish	Light Color	Power	Lense		Voltage	Driver	
VL-IV9	A Base	LG Light grey	White						
	B Base 2	DK Dark grey	W24 2400K	11W	8°	12°	UNIV 100-264Vac	STD ON/OFF	
	C Pole Arm	WH White	W27 2700K	20W	20°	30°	12 12Vdc		
	F Nut	BK Black	W30 3000K		45°	60°			
		RAL Any RAL color	W40 4000K		15x30°	10x60°			
				W60 6000K					
				Single Color (SC)					
				R Red	11W	8°	12°	UNIV 100-264Vac	STD ON/OFF
				B Blue	20W	20°	30°	12 12Vdc	
				G Green		45°	60°		
			A Amber		15x30°	10x60°			

Reference example

VL-IV9-C-WH-G-20W-10x60-12-STD

Variations



A
Base



B
Base 2




C
Pole Arm
D=45mm




F
Nut (M10x1,5mm)




Dimensions




TYPE A




TYPE B



TYPE C



TYPE F



Accessories

Code	Accessories
------	-------------

VL-IV9

HO Hood
VS Visor


Code	Accessories
------	-------------

VL-IV9


***SPK** SPIKE
***1BR** Bracket for 1 projector
***2BR** Bracket for 2 projector
***BX** Elevated Box
***CBLX** Special length cable

** Must be used with Type F*
** Must be used with Type C*
** Must be used with Type C*
** Must be used with Type F*
** Instead of X, put length of cable needed*
Example: VL-IV9-CBL-10m


HO




SPK




BX



VS



1BR



2BR

