KUBO.MIN













CREE XP-G





FAILURE RATE



















KUBO SERIES

References


Code	Finish	Light Color	Power	Lens	se	Voltage	Driver
VL-KUB.MIN	LG Light grey DK Dark grey WH White BK Black RAL Any RAL color	White W24 2400K W27 2700K W30 3000K W40 4000K W60 6000K	6W	8° 20° 40° 15x30°	12° 30° 60° 10x70°	UNIV 12 12Vdc	STD ON/OFF R Remote 230V R010 Remote 0-10V RD Remote DALI RCAS Remote Casambi
		Single Color (SC) R Red B Blue G Green A Amber	6W	4,5° 12° 30° 60° 10x70°	8° 20° 40° 5x20°	UNIV 1 2 12Vdc	STD ON/OFF R Remote 230V R010 Remote 0-10V RD Remote DALI RCAS Remote Casambi
		RGBW RGBW3 4 in 1 Chip RGB+W3000K	6W	20° 60° 15x60°	40° 15x30°	12 12Vdc	RD Remote DALI DMX RCAS Remote Casambi
		RGBW4 4 in 1 Chip RGB+W4000K					TOTAL TOTAL CUSUMD


Reference example

VL-KUB.MIN-WH-W24-10W-12°-UNIV-STD

Dimensions







Accesories

Code	Accesories
VL-KUB.MIN	HC Honeycomb Grid



Code	Accesories				
VL-KUB.MIN	*POLE Pole *CLP Clap *VSR Visor *CBLX Special length cable				

* Instead of X, put length of cable needed Example: VL-KUB.MIN-CBL-10m



