

LINNEA.30



IP66	IK09	CREE XP-G	RECYCLE
FAILURE RATE < 0,1% after 25,000h	LIFE TIME Tested over 50,000h	MIN -20°C MAX 55°C	CLASE I

LINNERS
LINNEA SERIES

References

Code	Finish	Light Color	Lenght-Power	Lense		Voltage	Driver
VL-LN.30	LG Light grey RAL Any RAL color	White					
		W24 2400K	300mm-6W	20°	30°	24 24Vdc	STD ON/OFF
	W27 2700K	500mm-9W	45°	60°	R010 Remote 0-10V		
	W30 3000K	500mm-12W	25x45°		RD Remote Dali		
	W40 4000K	1000mm-18W	CAS Casambi				
	W60 6000K	1000mm-24W					
	Single Color (SC)						
	R Red	300mm-6W	20°	30°	24 24Vdc	STD ON/OFF	
	B Blue	500mm-9W	45°	60°		R010 Remote 0-10V	
	G Green	500mm-12W	25x45°			RD Remote Dali	
	A Amber	1000mm-18W	CAS Casambi				
		1000mm-24W					
	RGBW						
	RGBW3	300mm-6W	20°	30°	24 24Vdc	DMX	
	4 in 1 Chip	500mm-9W	45°	60°			
RGB+W3000K	500mm-12W	25x45°					
RGBW4	1000mm-18W						
4 in 1 Chip	1000mm-24W						
RGB+W4000K							

Reference example


VL-LN.30-RGBW3-1000mm-24W-60-24-DMX

Dimensions



Accessories

Code	Accessories
VL-LN.30	HC Honeycomb Grid



Code	Accessories
VL-LN.30	IO In&out cable with connectors *CBLX Special length cable

** Instead of X, put length of cable needed
Example: VL-LN40-CBL-10m*